

# MATERIAL SAFETY DATA SHEET

YP900B

## SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NUMBER

YP900B

### PRODUCT NAME

Self Drying Primer of Ivory White

### MANUFACTURER'S NAME

SHANGHAI YOO-POINT CHEMICAL MANUFACTURING CO., LTD,

Shanghai 201706 China

### Telephone Numbers and Websites

Product Information	<a href="http://www.yoo-point.cn">www.yoo-point.cn</a>
Regulatory Information	(8621) - 59783999
Medical Emergency	(8621) - 59783373

## SECTION 2-COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
10	66742-88-7	White Spirit		2 mm
		ACGIH TLV	100 PPM	
		OSHA PEL	100 PPM	
13	64741-65-7	Mineral Spirit		2 mm
		ACGIH TLV	100 PPM	
		OSHA PEL	100 PPM	
20	1330-20-7	Xylene-mixed		
		ACGIH TLV/TWA	100 PPM	435 mg/cu.m.
		ACGIH TLV/STEL	150 PPM	655mg/cu.m.
		OSHA PEL/TWA	100PPM	435mg/cu.m.
		OSHA PEL/STEL	150 PPM	655mg/cu.m.
0.2	71-36-3	N-butyl Alcohol		
		ACGIH TLV/CEILING	50 PPM	150mg.cu.m.skin
		OSHA PEL/CEILING	50 PPM	150mg.cu.m.skin
20	140807-96-6	Talc		
		ACGIH TLV	2mg/m3 as Resp.Dust	
		OSHA PEL	2mg/m3 as Resp.Dust	
22	13463-67-7	Titanium Dioxide		
		ACGIH TLV	10mg/m3 as Dust	
		OSHA PEL	10mg/m3 Total Dust	
		OSHA PEL	5mg/m3 Respirable Fraction	

## SECTION 3 — HAZARDS IDENTIFICATION

### ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

### EFFECTS OF OVEREXPOSURE

**EYES:** Irritation.

**SKIN:** Prolonged or repeated exposure may cause irritation.

**INHALATION:** Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

### CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

## SECTION 4 — FIRST AID MEASURES

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

## SECTION 5 — FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL	FLAMMABILITY CLASSIFICATION
104 °F PMCC	0.9	6.0	Combustible, Flash above 99 and below 200 °F

### EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

### SPECIAL FIRE FIGHTING PROCEDURES

### HMIS Codes

Health	2
Flammability	2
Reactivity	0

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure, build-up and possible auto ignition or explosion when exposed to extreme heat.

## **SECTION 6 — ACCIDENTAL RELEASE MEASURES**

### **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

## **SECTION 7 — HANDLING AND STORAGE**

### **STORAGE CATEGORY**

DOL Storage Class II

### **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE** Contents

are COMBUSTIBLE. Keep away from heat and open flame. Consult

NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## **SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are

ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

### **VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

### **RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

### **PROTECTIVE GLOVES**

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

#### EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

#### OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

### SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	1468 g/l
SPECIFIC GRAVITY	1.42
BOILING POINT	115 - 201 °C
MELTING POINT	Not Available
VOLATILE VOLUME	78%
EVAPORATION RATE	Slower than ether
VAPOR DENSITY	Heavier than air
SOLUBILITY IN WATER	N.A..
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)	
	309g/l Less Water and Federally Exempt Solvents
	309g/l Emitted VOC

### SECTION 10 — STABILITY AND REACTIVITY

STABILITY — Stable

#### CONDITIONS TO AVOID

None known.

#### INCOMPATIBILITY

None known.

#### HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

#### HAZARDOUS POLYMERIZATION

Will not occur

### SECTION 11 — TOXICOLOGICAL INFORMATION

#### CHRONIC HEALTH HAZARDS

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Cobalt and cobalt compounds are classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is inadequate evidence in humans for its carcinogenicity.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during

the use of products in which titanium is bound to other materials, such as paint."

#### TOXICOLOGY DATA

<u>CAS Number</u>	<u>Ingredient</u>			
66742-88-7	White Spirit	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
64741-65-7	Mineral Spirit	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
1330-20-7	Xylene-mixed	LD50,Oral	4300 mg.kg (RAT)	
		LD50,Dermall	> 1700 mg.kg (RABBIT)	
		LC50,Inhalation	5000 PPM/4H (RAT)	
71-36-3	N-butyl Alcohol	LD50,Oral	2500 mg.kg (RAT)	
		LD50,Dermall	3400mg.kg (RABBIT)	
		LC50,Inhalation	> 8000 PPM/8H (RAT)	
140807-96-6	Talc	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

## SECTION 12 — ECOLOGICAL INFORMATION

#### ECOTOXICOLOGICAL INFORMATION

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

#### US Ground (DOT)

May be classified as a Combustible Liquid for U.S. Ground.

UN1263, PAINT, 3, PG III, (ERG#128)

DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities

Xylenes (isomers and mixture) 100 lb RQ

**Bulk Containers may be shipped as (check reportable quantities):**

UN1263, PAINT, COMBUSTIBLE LIQUID, PG III, (ERG#128)

**Canada (TDG)**

May be classified as a Combustible Liquid for Canadian Ground.

UN1263, PAINT, CLASS 3, PG III, (ERG#128)

**IMO**

UN1263, PAINT, CLASS 3, PG III, (38 C c.c.), EmS F-E, S-E

## SECTION 15 — REGULATORY INFORMATION

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

**CAS No. CHEMICAL/COMPOUND % by WT % Element**

Cobalt Compound 0.1 0.02

**CALIFORNIA PROPOSITION 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION**

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.**